

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 May 2002 (10.05.2002)

PCT

(10) International Publication Number
WO 02/36680 A1

(51) International Patent Classification⁷: C08L 23/06,
23/08, C08K 3/00, H01B 3/44

(21) International Application Number: PCT/IB01/02742

(22) International Filing Date: 25 October 2001 (25.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0026706.2 1 November 2000 (01.11.2000) GB

(71) Applicant (for all designated States except US): EC ER-
DOLCHEMIE GMBH [DE/DE]; Alte Strasse 201, 50769
Cologne (DE).

(71) Applicant and

(72) Inventor: BILES, Olivier [FR/FR]; Le Touret de Vallier,
Bat C, Appt 6, F-13500 Martigues (FR).

(74) Agent: HAWKINS, David; BP International Limited,
Patents & Agreements, Chertsey Road, Sunbury on
Thames, Middlesex TW16 7LN (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU,
ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii)) for the following designations AE,
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IN, IS, JP, KE, KG, KP,
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE,
SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU,
ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL,
SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ,
MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE,
DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR),
OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG)
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **CROSSLINKABLE ETHYLENE POLYMER BLENDS**

(57) Abstract: Novel polymer blends are provided comprising crosslinkable polymeric composition comprising (a) A blend of: (i) 100 parts by weight of LDPE component (A) (ii) 1-200 parts by weight of HDPE component (B) having a polydispersity (Mw/Mn) of <12. (iii) 0-100 parts by weight of an EVA copolymer (C). Particularly preferred compositions comprise blends having HDPE components having a polydispersity of <7. The blends are particularly suitable for use in automotive cables together with flame retardants and antioxidants. The crosslinked cables show an acceptable combination of improved temperature resistance and mechanical properties, abrasion resistance, reduced halogen content, ease of use and processability.

WO 02/36680 A1

CROSSLINKABLE ETHYLENE POLYMER BLENDS

The present invention relates to novel polymer blends and in particular to blends particularly suitable for use as components of cross-linkable compositions for use as automotive cables. The novel polymer blends allow such cross-linkable compositions to impart improved mechanical properties and processability in such cables.

5 At present automotive cables are commonly insulated with polyvinyl chloride and are designed to service temperatures of 100°C. However, increased working temperatures and reduced space under automobile bonnets have led the industry to increase the service temperature of automotive wires. In order to meet the new criteria of higher temperatures, for example in the range 105 - 125°C, automotive wires need to
10 exhibit improved thermal resistance. As a consequence of this increased service temperature and the drive to reduce the use of chlorinated compounds in automobile manufacturing, polyvinyl chloride (PVC) is no longer a preferred material for automotive wiring.

15 In addition to the thermal resistance requirement of the new automotive specifications, the wires must also offer high mechanical properties, high abrasion resistance, excellent resistance to oils and solvents and resistance to fire.

20 The known alternatives to PVC for the insulation of automotive wires, suffer from several drawbacks. Compounds based on halogen free retardants suffer from poor processability and inferior mechanical properties compared to PVC compounds. Sioplas compounds whether halogen-free or halogenated suffer from poor shelf life which can give rise to gel problems during extrusion.

It is one of the objects of the present invention therefore to provide a suitable

resin system for automotive cables having an acceptable combination of improved temperature resistance and mechanical properties, abrasion resistance, reduced halogen content, ease of use and processability.

5 US 5439965 describes polymeric compositions useful as insulation for wire and cable products for example automotive applications. In particular crosslinkable polymeric compositions comprising copolymers of ethylene and vinyl esters are disclosed in combination with flame retardant materials. Similar materials are described in US 4477523 and US 4255303.

10 US 4035325 describes flame retardant combinations of antimony trioxide and hexabromocyclododecane improved by the addition of certain organometallic compounds.

It has now been discovered that novel blends comprising high density polyethylenes (HDPE) having polydispersity (M_w/M_n) of < 12 may be suitably used as components of cross-linkable polymeric compositions for use as automotive cables. In 15 particular novel polymer blends comprising such HDPE with a low density polyethylene (LDPE) and optionally an ethylene vinyl acetate (EVA) component have been developed.

Thus according to the present invention there is provided a crosslinkable polymeric composition comprising a blend of:

- 20 (i) 100 parts by weight LDPE component (A)
(ii) 1 – 200 parts by weight HDPE component (B) having a polydispersity (M_w/M_n) of < 12 , and
(iii) 0 - 100 parts by weight of an EVA component (C).

A preferred composition comprises a blend of:

- 25 (i) 100 parts by weight LDPE component (A)
(ii) 1 – 100 parts by weight HDPE component (B) having a polydispersity (M_w/M_n) of < 12 , and
(iii) 0 - 100 parts by weight of an EVA component (C).

A highly preferred composition comprises a blend of:

- 30 (i) 100 parts by weight LDPE component (A), and
(ii) 1 – 60 parts by weight HDPE component (B) having a polydispersity (M_w/M_n) of < 12 .

A particularly preferred composition comprises a blend of:

- (i) 100 parts by weight LDPE component (A), and
- (ii) 25 - 55 parts by weight HDPE component (B) having a polydispersity (M_w/M_n) of < 12 .

5 A most preferred composition comprises a blend of:

- (i) 100 parts by weight LDPE component (A), and
- (ii) 35 - 55 parts by weight HDPE component (B) having a polydispersity (M_w/M_n) of < 12 .

10 The LDPE component (A) has a density in the range $0.918 - 0.940 \text{ g/cm}^3$, preferably a density in the range $0.923 - 0.940 \text{ g/cm}^3$, most preferably a density in the range $0.926 - 0.940 \text{ g/cm}^3$, and even more preferably a density in the range $0.930 - 0.940 \text{ g/cm}^3$.

15 The LDPE component (A) has a MFR in the range $0.1 - 3 \text{ g/10 minutes}$, more preferably a MFR in the range $0.15 - 2 \text{ g/10 minutes}$, and most preferably a MFR in the range $0.5 \text{ to } 1.5 \text{ g/10 minutes}$.

The HDPE component (B) has a density in the range $0.940 \text{ to } 0.965 \text{ g/cm}^3$, preferably a density in the range $0.940 - 0.960 \text{ g/cm}^3$, and most preferably a density in the range $0.950 - 0.960 \text{ g/cm}^3$.

20 The HDPE component (B) has a MFR in the range $1 - 10 \text{ g/10 minutes}$, and preferably a MFR in the range $2 - 6 \text{ g/10 minutes}$.

The preferred HDPE component (B) has a polydispersity (M_w/M_n) < 9 and a particularly preferred polydispersity (M_w/M_n) < 7 .

The EVA component (C) has a vinyl acetate (VA) content in the range $1 - 45 \%$ by weight and a MFR in the range $0.1 - 50 \text{ g/10 minutes}$.

25 The LDPE, HDPE and EVA copolymer may suitably be prepared using well known polymerisation catalysts and processes.

30 The melt flow rate (MFR) measurements are made according to ISO 1133 condition D and density measurements are made according to ISO 1183 method D. Weight average molecular weight (M_w) and number average molecular weight (M_n) were measured by Gel Permeation Chromatography (GPC) using a Waters 150C instrument using a mobile phase of 1,2,4-trichlorobenzene at 140°C . Sample solutions were made by dissolving the polymers in the same solvent. All solutions were tested

without filtering. Molecular weights were calculated as polyethylene equivalents. The polydispersity is defined as the ratio of Mw to Mn.

When used in combination with an antioxidant system (D) and a flame retardant package (E) the novel blends of the present invention result in crosslinkable polymeric compositions having the required combination of properties suitable for use as automotive cables having a reduced halogen content compared to PVC.

Thus according to another aspect of the present invention there is provided an automotive cable comprising a crosslinkable polymeric composition comprising

(a) a blend of

- (i) 100 parts by weight LDPE component (A)
- (ii) 1 - 200 parts by weight HDPE component (B) having a polydispersity (Mw/Mn) of < 12, and
- (iii) 0 - 100 parts by weight of an EVA copolymer (C).

(b) an antioxidant system (D), and

(c) a flame retardant material (E).

A preferred crosslinkable composition comprises a blend of:

- (i) 100 parts by weight LDPE component (A)
- (ii) 1 - 100 parts by weight HDPE component (B) having a polydispersity (Mw/Mn) of < 12, and
- (iii) 0 - 100 parts by weight of an EVA copolymer (C).

A highly preferred crosslinkable composition comprises a blend of:

- (i) 100 parts by weight LDPE component (A), and
- (ii) 1 - 60 parts by weight HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

A particularly preferred crosslinkable composition comprises a blend of:

- (i) 100 parts by weight LDPE component (A), and
- (ii) 35 - 55 parts by weight HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

A most preferred crosslinkable composition comprises a blend of:

- (i) 100 parts by weight LDPE component (A), and
- (ii) 25 - 55 parts by weight HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

The preferred LDPE and HDPE suitable for use in the crosslinkable compositions according to this aspect of the present invention have the densities and MFR described above.

The preferred HDPE have a polydispersity of < 9 and most preferably < 7 .

5 The antioxidant used as component (D) may be any conventional material but is preferably a combination of well known IrganoxTM materials. A combination of IrganoxTM 1010 and IrganoxTM MD1024 has been found to be particularly useful in the present invention.

10 A preferred antioxidant for use in the present invention comprises a mixture of Irganox MD 1024TM of concentration between 0.1 – 0.9 parts per hundred by weight of polymer blend and Irganox 1010TM of content 0.2 - 0.9 parts per hundred by weight of polymer blend. A particularly preferred antioxidant package comprises a mixture of Irganox MD 1024TM of concentration between 0.1 – 0.6 parts per hundred by weight of polymer blend and Irganox 1010TM of content 0.2 - 0.6 parts per hundred by weight of
15 polymer blend.

The flame retardant package (E) may be comprised of any conventional halogenated materials. As part of the flame retardant package (E) optionally a coagent may be used for increased efficiency of the flame retardant additive. Examples of suitable brominated agents are aromatic or aliphatic compounds typically containing an
20 amount of bromine in the range 70 – 90 %. Typical examples include polybrominated diphenyl ethers, hexabromocyclododecane, ethane-1,2-bis(pentabromophenyl), tetrabromophthalate diols and polyethers, tetrabromobisphenol A and derivatives. Typical examples of coagents include antimony trioxide, Zinc sulphide, Zinc oxide, Zinc borate and boric acid.

25 A particularly preferred flame retardant package for use in the present invention comprises a coagent of content 3 – 28 parts per hundred by weight of polymer blend and a brominated additive of content 9 - 55 parts per hundred by weight of polymer blend, most preferably with a coagent content of 6 – 20 parts per hundred by weight of polymer blend and a brominated additive of content 15 - 40 parts per hundred by weight of
30 polymer blend.

The use of such a flame retardant package provides limited interference with the crosslinking and extrusion properties of the novel polymer blend and allows the

mechanical properties and abrasion requirements of automotive cables to be achieved.

The polymeric composition may be extruded and crosslinked by use of a one or two step silane crosslinking process, a peroxide crosslinking process or an irradiation crosslinking process. Optionally a promoter to enhance irradiation crosslinking may be incorporated.

Suitable one step silane procedures include dry silane or liquid silane injection and the two step silane procedure may be the SioplasTM process described in US 3646155. Crosslinking procedures are well known and may be illustrated in EP 426073.

The present invention will now be further illustrated by reference to the following examples:

Example 1: Novel Blend Formulation

Blend Component	Parts by weight
LDPE: MFR =1 g/10minutes, Density= 0.934 g/cm ³	100
HDPE: MFR =4 g/10minutes, Density= 0.960 g/cm ³ density, Mw/Mn=6	82

Example 2: Novel Blend Formulation

Blend Component	Parts by weight
LDPE: MFR =1 g/10minutes, Density= 0.934 g/cm ³	100
HDPE: MFR =4 g/10minutes, Density= 0.960 g/cm ³ , Mw/Mn =6	50

Example 3: Novel Blend Formulation

Blend Component	Parts by weight
LDPE: MFR =1 g/10minutes, Density= 0.934 g/cm ³	100
HDPE: MFR =4 g/10minutes, Density= 0.957 g/cm ³ , Mw/Mn =6	50

Example 4: Novel Blend Formulation

Blend Component	Parts by weight
LDPE: MFR =1 g/10minutes, Density= 0.934 g/cm ³	100
HDPE: MFR =4 g/10minutes, Density= 0.957 g/cm ³ , Mw/Mn =6	43

Example 5: Novel Blend Formulation

5

Blend Component	Parts by weight
LDPE: MFR =1 g/10minutes, Density= 0.934 g/cm ³	100
HDPE: MFR =4 g/10minutes, Density= 0.954 g/cm ³ , Mw/Mn =5	60
EVA copolymer, MFR =4.5 g/10minutes, 24% weight VA	20

Example 6: Use of Novel blends as components of silane crosslinked automotive cables

The novel polymer blends above when compounded with an antioxidant system and flame retardant package indicated below:

10

Composition	Parts by weight
Novel Polymer blend (example 1 - 5)	100
Irganox MD 1024	0.6
Irganox 1010	0.6
Antimony trioxide	14.5
decabromodiphenyl oxide	28.9

15

using a twin screw extruder (40 mm, 21 L/D, counter-rotating) with the following compounding settings:

Settings	
Temperature zone 1 (°C)	160
Temperature zone 2 (°C)	175
Temperature zone 3 (°C)	180
Temperature zone 4 (°C)	190
Temperature zone 5 (°C)	190
Temperature zone 6 (°C)	190
Temperature zone 7 (°C)	190
Output (kg/h)	15

- 5 give formulations suitable for use as a crosslinkable automotive formulation.

These formulations when extruded on a 45 mm 24 L/D extruder with addition of 2 % of Dry Silane masterbatch 7030 DS 80 from PolyOne (one step silane crosslinking) give wires suitable for use in automotive cables.

- Extruder temperatures (°C):

Z1	Z2	Z3	Z4	Z5	Z6	Head	Die	Screw
150	160	175	210	230	240	240	250	80

10

- screw design : Elise
- extrusion tools : 3 angle die and wire guide
- speed of the line : 50 m / min
- thickness of the insulating layer : 0.3 mm
- 15 - diameter of the copper core : 0.8 mm
- temperature of the compound at the entrance of the feed zone : cold (23 °C)
- temperature of the cooling trough : 60 °C

3 - Cable properties:

Crosslinking performance in air (according to IEC 811-2-1):

20

After 4 hours in water at 80°C :

Hot set test at 200 °C, 20 N/cm² (%): <150%

Mechanical properties before ageing (according to IEC 811-1-1):

Tensile stress at break (MPa)	>12
Elongation at break (%)	>300

Winding test after ageing 10 days @ 150°C on copper (according to IEC 811-1-2):

5 No cracks

Flame test (according to ISO 6722):

Pass

Scrape abrasion resistance (according to ISO 6722):

Number of cycles before failure : > 300

10 Example 7: Use of Novel blends as components of irradiation crosslinked automotive cables

The novel polymer blends above when compounded with an antioxidant system and flame retardant package indicated below:

Composition	Parts by weight
Novel Polymer blend (example 1 - 5)	100
Irganox MD 1024	0.6
Irganox 1010	0.6
Silica supported triallylcyanurate (TAC). Contains 70% triallylcyanurate.	5.3
Antimony trioxide	15.2
decabromodiphenyl oxide	30.4

15

20

using a twin screw extruder (40 mm, 21 L/D, counter-rotating) using the following compounding settings:

Settings	
Temperature zone 1 (°C)	160
Temperature zone 2 (°C)	175
Temperature zone 3 (°C)	180
Temperature zone 4 (°C)	190
Temperature zone 5 (°C)	190
Temperature zone 6 (°C)	190
Temperature zone 7 (°C)	190
Output (kg/h)	15

- 5 give formulations suitable for use as an irradiation crosslinkable automotive formulation.

These formulations when extruded on a 45 mm 24 L/D extruder under the following conditions and crosslinked by irradiation under the following conditions give wires suitable for use in automotive cables.

- 10 - Extruder temperatures (°C):

Z1	Z2	Z3	Z4	Z5	Z6	Head	Die	Screw
150	160	175	210	230	240	240	250	80

- Screw design : Elise
- Extrusion tools : 3 angle die and wire guide
- Speed of the line : 50 m / min

- 15
- Thickness of the insulating layer : 0.3 mm
 - Diameter of the copper core : 0.8 mm
 - Temperature of the compound at the entrance of the feed zone : cold (23 °C)
 - Temperature of the cooling trough : 60 °C
 - Irradiation energy: 20 Megarads

- 20 4 - Cable properties:

Crosslinking performance (according to IEC 811-2-1):

Hot set test at 200 °C, 20 N/cm² (%): <150%

Mechanical properties before ageing (according to IEC 811-1-1):

Tensile stress at break (MPa)	>12
Elongation at break (%)	>300

5 Winding test after ageing 10 days @ 150°C on copper (according to IEC 811-1-2):

No cracks

Flame test (according to ISO 6722):

Pass

Scrape abrasion resistance (according to ISO 6722):

10 Number of cycles before failure : > 300

15

20

25

30

Claims

1. A crosslinkable polymeric composition comprising

(a) a blend of:

(i) 100 parts by weight of LDPE component (A)

(ii) 1 - 200 parts by weight of HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

(iii) 0 - 100 parts by weight of an EVA copolymer (C).

2. A composition according to claim 1 wherein the blend comprises

(i) 100 parts by weight of LDPE component (A)

(ii) 1 - 100 parts by weight of HDPE component (B) having a polydispersity (Mw/Mn) of < 12, and

(iii) 0 - 100 parts by weight of an EVA copolymer (C).

3. A composition according to either of the preceding claims wherein the blend comprises

(i) 100 parts by weight of LDPE component (A) and

(ii) 1 - 60 parts by weight of HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

4. A composition according to any of the preceding claims wherein the blend comprises

(i) 100 parts by weight of LDPE component (A) and

(ii) 25 - 55 parts by weight of HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

5. A composition according to any of the preceding claims wherein the blend

comprises

- (i) 100 parts by weight of LDPE component (A) and
- (ii) 35 - 55 parts by weight of HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

5 6. A composition according to any of the preceding claims wherein the HDPE has a polydispersity of < 9.

7. A composition according to any of the preceding claims wherein the HDPE has a polydispersity of < 7.

8. A composition according to any of the preceding claims wherein the HDPE has a density in the range 0.940 – 0.960 g/cm³.

9. A composition according to any of the preceding claims wherein the HDPE has a density in the range 0.950 – 0.960 g/cm³.

10. A composition according to any of the preceding claims wherein the HDPE has a MFR in the range 2 – 6 g/ 10 minutes.

11. A composition according to any of the preceding claims wherein the LDPE has a density in the range 0.926 – 0.940 g/cm³.

12. A composition according to any of the preceding claims wherein the LDPE has a density in the range 0.930 – 0.940 g/cm³.

13. A composition according to any of the preceding claims wherein the LDPE has a MFR in the range 0.15 – 2 g/10 minutes.

14. A composition according to any of the preceding claims wherein the EVA component (C) has a vinyl acetate (VA) content in the range 1 – 45 % by weight and a MFR in the range 0.1 – 50 g/10 minutes.

15. An automotive cable comprising a crosslinkable polymeric composition comprising

(a) A blend of:

- (i) 100 parts by weight of LDPE component (A)
- (ii) 1 – 200 parts by weight of HDPE component (B) having a polydispersity (Mw/Mn) of < 12.

(iii) 0 – 100 parts by weight of an EVA copolymer (C),

(b) An antioxidant system (D) and

(c) A flame retardant material (E).

16. An automotive cable according to claim 14 comprising a crosslinkable polymeric composition as claimed in any of claims 2 to 14.
17. A cable according to claims 15 or 16 wherein the flame retardant material (E) comprises a halogenated material.
- 5 18. A cable according to any of claim 17 wherein the halogenated material is present in amount of 15 – 40 parts per hundred of the polymer blend.
19. A cable according to any of claims 15 - 18 wherein the flame retardant material (E) includes a coagent.
20. A cable according to claim 19 wherein the coagent is present in amount of 6 –
10 20 parts per hundred of the polymer blend.
21. A cable according to claim 19 wherein the coagent is antimony trioxide.
22. A cable according to claims 15 – 21 wherein the antioxidant system (D) is present in amount of 0.2 – 0.9 parts per hundred of the polymer blend.
23. A polymeric composition according to any of the preceding claims crosslinkable
15 by use of a silane, a peroxide or an irradiation crosslinking process.

20

25

30

INTERNATIONAL SEARCH REPORT

Inte 1al Application No
PCT/IB 01/02742

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C08L23/06 C08L23/08 C08K3/00 H01B3/44

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C08L H01B C08K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 956 567 A (KRACKELER JOSEPH J ET AL) 11 May 1976 (1976-05-11) abstract column 1, line 8 - line 14 column 1, line 34 - column 2, line 19 column 2, line 34 - line 58 column 2, line 59 - column 3, line 50 column 4, line 12 - line 17 --- -/-	1-9, 11-13, 15-23

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

22 March 2002

Date of mailing of the international search report

10/04/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Droghetti, A

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/IB 01/02742

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99 65957 A (EGASHIRA TOSHIAKI ;SAKAMOTO KAZUYUKI (JP); WAKAYAMA MASAHIRO (JP);) 23 December 1999 (1999-12-23) abstract	1-23
E	& EP 1 153 948 A (JAPAN POLYOLEFINS CO LTD) 14 November 2001 (2001-11-14) abstract page 3, line 5 - line 11 page 6, line 15 - line 18 page 7, line 24 - line 26 page 8, line 3 - line 15 page 12, line 19 -page 14, line 17 page 16, line 55 -page 18, line 55 page 42, line 15 -page 44, line 42 claims 27,29,30	
X	EP 0 546 841 A (NIPPON PETROCHEMICALS CO LTD) 16 June 1993 (1993-06-16) abstract page 2, line 3 - line 11 page 3, line 14 - line 45 page 4, line 1 - line 28 page 7, line 9 - line 12 page 7, line 44 -page 8, line 2 examples A1,B1-1,B2	1-23

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 01/02742

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3956567	A	11-05-1976	US 3900533 A	19-08-1975
			AT 326925 B	12-01-1976
			AT 51474 A	15-03-1975
			BE 811666 A1	27-08-1974
			DE 2410475 A1	03-10-1974
			FR 2220549 A1	04-10-1974
			GB 1466184 A	02-03-1977
			IT 1007305 B	30-10-1976
			JP 49119945 A	15-11-1974
			NL 7402583 A	09-09-1974
			SE 388428 B	04-10-1976
			SU 578896 A3	30-10-1977
WO 9965957	A	23-12-1999	JP 2000072824 A	07-03-2000
			JP 2000053819 A	22-02-2000
			JP 2000053821 A	22-02-2000
			CN 1305502 T	25-07-2001
			EP 1153948 A1	14-11-2001
			WO 9965957 A1	23-12-1999
			JP 2000090743 A	31-03-2000
EP 0546841	A	16-06-1993	CA 2084491 A1	11-06-1993
			CN 1074454 A , B	21-07-1993
			DE 69224712 D1	16-04-1998
			DE 69224712 T2	02-07-1998
			EP 0546841 A1	16-06-1993
			JP 5239281 A	17-09-1993
			JP 5247278 A	24-09-1993
			KR 233963 B1	15-12-1999
			US 5418272 A	23-05-1995
			JP 5262931 A	12-10-1993
			JP 5262927 A	12-10-1993